



6 P + T

Ampères

Pôles

















230 V  
50/60 Hz  
7 pôles  
9h

400 V  
50/60 Hz  
7 pôles  
6h

500 V  
50/60 Hz  
7 pôles  
7h



Numéros d'article

	16	7	110 709	110 706	110 707	10	251
	32	7	130 709	130 706	130 707	10	349
<b>Socles en saillie IP 44 , fixation extérieure, 1 entrée de câble en haut</b>							
	16	7	111 709	111 706	111 707	5	449
	32	7	131 709	131 706	131 707	5	518
<b>Socles en saillie IP 44 , fixation intérieure, entrées de câbles défonçables, 2 en haut et 2 en bas</b>							
	16	7	210 709	210 706	210 707	10	203
	32	7	230 709	230 706	230 707	10	291
<b>Fiches IP 44 , avec embout souple</b>							
	16	7	610 709	610 706	610 707	10	204
	32	7	630 709	630 706	630 707	10	287
<b>Socles de connecteur en saillie IP 44 , fixation extérieure, 1 entrée de câble en haut</b>							
	16	7	611 709	611 706	611 707	10	204
	32	7	631 709	631 706	631 707	10	305
<b>Socles de connecteur de tableau coudés IP 44 , partie arrière vissée</b>							
	16	7	310 709	310 706	310 707	10	245
	32	7	330 709	330 706	330 707	10	339
<b>Prolongateurs IP 44 , avec embout souple</b>							
	16	7	411 709	411 706	411 707	10	218
	32	7	431 709	431 706	431 707	10	277
<b>Socles de tableau droits IP 44 , plastron vissé</b>							
	16	7	514 709	514 706	514 707	10	240
	32	7	534 709	534 706	534 707	10	330
<b>Socles de tableau coudés IP 44 , partie arrière vissée</b>							